

RADOX® MILCAT

Databus cable for harsh environment



Characteristics



- CAT5 properties
- Optimized diameter for RJ45 and other connectors
- For fix and flexible applications
- Halogen free
- Complies with RoHS directives
- Robust design

Benefits

- Designed for harsh environment
- High speed solution
- Long life time
- Light weight and easy to process

Applications

- Military communication
- Industrial automation
- Other industrial applications in harsh environment



Technical properties	
Conductor	Tinned copper, flexible, EN 60228, class 5
Insulation	RADOX® PE Isolation
EMC screen	Aluminium tape, plastic laminated and tin-plated copper braid
Sheath	RADOX® PU, colour black
Impedance	100 Ω at 100 MHz
Voltage rating	300 V
Construction	4 x 2 x 26 AWG
Outer diameter	7.1 mm
Temperature range	-40 °C to +90 °C
Item no.	12585990

Media properties	
Very good resistance against	Oils and fuels
	Water and hydrolysis
	Weather and UV radiation
	Others on request

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS.

WAIVER

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

HUBER+SUHNER AG
 Low Frequency Division
 Tumbelenstrasse 20
 8330 Pfäffikon/Switzerland
 Tel. +41 44 952 2211
 Fax +41 44 952 2670
 info@hubersuhner.com

hubersuhner.com

